

## GRAPHICMASTER

1600HRS, 2100HRS, 2100COMBI/RS





1600HRS, 2100HRS, 2100COMBI/RS

- · Pneumatic (Air) Pressure Control
- Electronic/Pneumatic Roller Gap Control (Max.Gap 30mm)
- · Enhanced and Simplfied Control:
  - VFD (Vaccum Fluorescent Display) Control Panel
  - Master Control Knob for Top Temp., Bottom Temp., speed Control and Job Mode.
  - Multi-functional Foot Switch : Depending on the number of steps, Switching funtion from Roller Engage, Roller Release, Reverse, etc.
- Removable rear cross web trimmer







0

Ω

a

0

co

\_

a

3

\_

o

0

9

Φ

O

5

9

0

0

0





## 2.1m Wide Format Laminator

GraphicMaster laminator series proudly boasts 2.1m wide hot laminating machine with in the family. Adapting a new engineering concept for sure and better laminating result and simple to use operating panel, the GraphicMaster series offers convenience and value to users in the Large Format market and the graphics industry.

## **SPECIFICATION**

Model Name	1600HRS	2100HRS	2100COMBI/RS
Power Consumption(Watts)	7,500	10,000	3,000
Dimension(W×L×H)mm	2110x850x1395	2800x994x1540	2800x994x1540
Max.Laminating Width(mm)	1600	2100	2100
Heating System		Infrared Heater	
Temperature Control	Proportional Control by 8Bit Microprocessor (IR Sensor)		
Operating Temperature(*C)	0~160	0~160	0~100
Laminating speed(mm/min)	3,000	5,000	3,000
Power Supply	380~400V/3 50~60Hz	380~400V/3 50~60Hz	220~240V/3 50~60Hz

GMP reserves the right to after change specifications without prior notice

